

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 02-172220

(43)Date of publication of application : 03.07.1990

(51)Int.Cl.

H01L 21/266

H01L 21/331

H01L 27/088

H01L 29/73

(21)Application number : 63-325791

(71)Applicant : HITACHI LTD

(22)Date of filing : 26.12.1988


(72)Inventor : OYU SHIZUNORI  
SUZUKI TADASHI  
KASHU NOBUYOSHI  
ADACHI YASUKO

## (54) ION IMPLANTATION

### (57)Abstract:

**PURPOSE:** To facilitate formation of a retrograded impurity introduced layer whose surface impurity concentration is controlled by a method wherein a first mask region composed of a mask material which blocks the implantation is provided on a substrate except the impurity introduced region and a second mask region composed of a patterned mask material is provided on the impurity introduced region.

**CONSTITUTION:** A mask material 3 on the impurity introduced region 2 of a semiconductor substrate 1 is patterned and a mask 6 which blocks implanted ions perfectly is provided on a region 5 into which the impurity is not introduced. The paths of the implanted ions 4 are changed by the patterned mask material 3 on the impurity introduced region 2 and the impurity ions are implanted into the surface of the semiconductor substrate 1 with various angles and energies. In other words, if the implanted ions 4 come close to the mask 3 of the impurity introduced region 2, they are scattered in the mask 3 and the impurity ions 4 coming out of the mask 3 is implanted into the substrate 1 with various angles and energies. With this constitution, a region 17 having uniform impurity concentration can be formed near the surface of the substrate 1.



## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]